

Object: TOTALI

| | NAME | | Description | Measurement unit | Quantity |
|---|---|------------------|--|------------------|----------|
| 1 | Frieze  | frieze | The frieze of the building consists of composite flat panels with special color blue with gloss. H = 870 mm. Complete with a subsystem for attaching to building structures and hardware. | M2 | 5.5 |
| 2 | Frieze  | frieze | The frieze of the building consists of composite flat panels with special color blue with gloss. H = 615 mm. Complete with a subsystem for attaching to building structures and hardware. | M2 | 9 |
| 3 | 3D letter (sign)  | 3D letter (sign) | Formed mortise in the frieze of the building letters "Express" (English) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 9 letters. | Piece | 7 |
| 4 | 3D letter (sign)  | 3D letter (sign) | Formed mortise in the frieze of the building letters "Express" (Georgian Language) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 7 letters. | Piece | 8 |
| 5 | Aluminum profile  | Aluminum profile | The profile of the junction of the frieze to the building in the upper part is made of aluminum with a polymer coating (white), h = 200mm | M2 | 2 |
| 6 | Steel parapet  | Steel parapet | Parapet 700 mm wide made of galvanized steel 0.5 mm thick. Without an internal metal frame. Fabrication at a construction site. | M2 | 7 |
| 7 | Mood lightning  | Mood lightning | A strobe with LED backlight to illuminate the frieze of the building. | M | 14.20 |
| 8 | 3D "Gulf logo"  | 3 D sign | 3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting. | Piece | 1.00 |
| 7 | frieze  | frieze | The frieze of the canopy consists of galvanized steel flat panels with special color blue with gloss. H = 900 mm. Complete with a subsystem for fastening to a canopy metalware and hardware. | M2 | 45.00 |
| 8 | 3D letter (sign)  | 3D letter (sign) | 3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting. English sign | piece | 1.00 |

| | | | | | | |
|----|---------------------|---|------------------|--|-------|--------|
| 9 | 3D letter (sign) |  | 3D letter (sign) | 3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting. English sign | piece | 1.00 |
| 10 | Frieze corner |  | frieze | Canopy frieze corner , 700mm high, blue molded plastic or composite aluminium panels. Substructures are made of galvanized steel profiles. Mounting system without hardware and fasteners on the front surface. | piece | 3.00 |
| 11 | 3D letter (sign) |  | Sign | Formed mortise in the frieze of the building letters "express" (English) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 7 letters. | piece | 7.00 |
| 12 | 3D letter (sign) |  | Sign | Formed mortise in the frieze of the building letters "express" (Georgian) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 8 letters. | piece | 8.00 |
| 13 | Orange strobe light |  | strobe | Profile with LED illumination in compound casting, made of extruded aluminum with a polymer coating, on brackets. Includes front and backlight illumination. Designed to organize the illumination of the frieze around the perimeter of the canopy. Complete with hardware. (completed on three and a half sides of the canopy) | meter | 50.00 |
| | Ceiling |  | Ceiling | 0.7mm galvanized steel suspended ceiling composed of: white panel with a width of 325 mm, docking profile, metal frame made of galvanized pipe and fittings, hardware. | m2 | 201.00 |
| 17 | LED lightning |  | LED lightning | LED Light, built into the suspended ceiling. Rectangular or square. Degree of protection against environmental impact IP65-67, operating temperature range from -30 to +50 degrees. Easy removable design for maintenance and replacement. | piece | 12.00 |
| 19 | column cladding |  | Pillar cladding | Column cladding made of galvanized steel 1.6 mm thick, with a polymer coating. Complete with metal frame. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 4.8m, 8pcs | m2 | 67.00 |
| 19 | Price board |  | Totem | Ministel for 4 types of fuel. One-sided. Stela panels are made of 1.9 mm thick aluminum with polymer coating. Internal LED backlighting is made with white LEDs. The stela is equipped with an IR remote control for price lines and tempered glass. | Piece | 2.00 |

| | | | | | |
|----|--|-------------------|---|-------|-------|
| 19 | Steel trash bin  | trash bin | Combined service unit on a fuel platform made of polymer coated steel. Includes a towel holder, a washing station for washing glasses, a box for gloves and a garbage container | piece | 1.00 |
| 18 | steel parapet  | steel parapet | Galvanised steel parapet 0.5 mm thickness, without metal subsystem , made on the site | m2 | 25.00 |
| 19 | Aluminium profile  | Aluminium profile | Transitional profile of joining the frieze to the canopy ceiling h = 0.2m. Made of white polymer coated aluminum | m2 | 10.00 |
| 1 | Frieze  | frieze | The frieze of the car wash building consists of galvanized steel flat panels with special color blue with gloss. H = 750 mm. Complete with a subsystem for attaching to building structures and hardware. ONLY FRONT SIDE | m2 | 7.5 |
| 19 | column cladding  | Pillar cladding | Column cladding for car wash made of galvanized steel , 1.6 mm thick, with a polymer coating. Complete with metal frame. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 3.38m, 3pcs | m2 | 19.00 |