




- 1.The motor sheave and the pump sheave must be parallel.
- 2.When the discharge has longer pipe, it is not allowed to press all pipe's weight on the pump.Additional fixed support should be added.

14	GB/T898	Stud M24x120	4	8.8 D.Zn		
13	GB/T6170	Nut M42	16	8 D.Zn		
12	GB/T15389	Screw M42x500	4	4.8 D.Zn		
11	ZVZ-F-Y225-02	Motor Support	1	Q235A		
10	GB/T97	Washer 20	4	200HV D.Zn		
9	GB/T93	Washer 20	4	65Mn		
8	GB/T6170	Nut M20	4	8 D.Zn		
7	GB/T5782	Bolt M20x100	4	8.8 D.Zn		
6	280S/M-4	Motor 90kW/380V/50HZ/VFD	1			

Item	Code Name	Description	Q'ty	Material	Single	Total
					Weight	

Item	Code Name	Description	Q'ty	Material	Single	Total	Note
					Weight		
				Slurry Pump J3E5-AR-AX	ZVZ-J3E5-AR-AX-280-4-E		
Notes	Q'ty	Revision No.	By	Date			
Drawn	Drawn						
Check	Check						
Appro.	Appro.						
Date	Date						
				ZVZ Drive	Drawing Mark		
					Weight		
					Scale		
					S	A	2700Kg
							1:10
					Title Sheet		The Sheet
					 Hebei Aojin Machinery Co., Ltd.		

Drawings Only For Quotation  
2024.08.08

