

Product	qt
Single Mode plenum rated indoor/outdoor stranded at least 4 core cable,	250
Cat 6 E UTP LSZH	6675
1U 19" ETSI Fiber Optic Patch Panel with front Cable Manager ,rail system. 4 sSC duplex adapter Fiber bend radius control - < 35mm. Cable glands to secure the incoming fiber, allows min movement. For SM cable	4
42U 800X1200 Rack. perforated steel doors with locks, front side 2x Vertical Cable Managers. Fan Unit with 4 ventilator and thermostat, 230V, minimum durability 50 000h, minimum capacity 165m3/h. Grounding Bar, Grounding Accessories for doors. at least 1300kg weight load	1
12U 800X600 Rack. Wall mountable	3
UTP CAT6E 48 Port Patch Panel Place for Cable labels. 19" standard.	8
Wall mount Faceplate with UTP CAT6E socket.	340
Horizontal Cable Manager 1U, 19".	10
rack mount PDU, 5xUTE sockets, 230V AC, Maximum Load 16A, Power Bracket	5
Cat6 UTP Rj45 connector	50
SC-SC patchcords 1m single mode, Simplex, 9/125. LSZH Rated	10
SC-SC patchcords 2m single mode, Simplex, 9/125. LSZH Rated	10
6000VA/4500W, Smart-Online UPS,	1
1000BASE-SX SFP GBIC Module	20
Switch, 48x 10/100/1000 ports, 2x 1G RJ45 uplink-ports, 4x 1G SFP uplink-ports upgradable	6
Switch, 12x 10/100/1000 PoE+ ports, 2x 1G RJ45 uplink-ports, 2x 1G SFP uplink ports upgrada	4
Core Switch SFP BUNDLE 1PSU (Layer 3 Switch with 12 SFP Port)	1
Firewall, Network Security Applience, Firewall 20,000 Mbps, VPN1,700 Mbps	1
Antenas	3
Multiswitch 17/16	1
Universal DVB to IP module with DVB-S/S2/T/T2/C input	1
Bracket for antenna	3
Base unit with switch, 230 V AC	1
Redundant power supply 230 V AC	1
Panasonic KX-NS500UC PBX main unit for 160 Abonent	1
WIFI Dual-Band 2x2-2 Access point	28