

























Object: FONICHALA

	NAME		Description	Measurment unit	Quantity
Building (frieze L = 28.1mp, sheathed from three sides)					
1	Frieze 	frieze	The frieze of the building consists of galvanized steel flat panels with special color blue with gloss. H = 800 mm. with a subsystem for attaching to building structures and hardware.	M2	14
2	3D letter (sign) 	3D letter (sign)	Formed mortise in the frieze of the building letters "Express" (English) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 9 letters.	Piece	7
3	3D letter (sign) 	3D letter (sign)	Formed mortise in the frieze of the building letters "Express" (Georgian Language) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 7 letters.	Piece	8
4	Aluminum profile 	Aluminum profile	The profile of the junction of the frieze to the building in the upper part is made of galvanized steel with a polymer coating (white), h = 200mm	M2	3.4
5	Steel parapet 	Steel parapet	Parapet 700 mm wide made of galvanized steel 0.5 mm thick. Without an internal metal frame. Fabrication at a construction site.	M2	11.9
6	Mood lightning 	Mood lightning	A strobe with LED backlight to illuminate the frieze of the building.	M	17.00
7	3D "Gulf logo" 	3 D sign	3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting.	Piece	1.00
8	frieze 	frieze	The frieze of the canopy consists galvanized steel flat panels with special color blue with gloss. H = 900 mm. Complete with a subsystem for fastening to a canopy metalware and hardware.	M2	29.97
9	3D letter (sign) 	3D letter (sign)	3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting. English sign	piece	1.00

10	3D letter (sign) 	3D letter (sign)	3D sign on the facade of the building ". D 790mm. Made of molded acrylic with UV printing and applique. With internal LED lighting. English sign	piece	1.00
11	Frieze corner 	fieze	Canopy frieze corner , 900mm high, blue molded galvanized steel panels. Substructures are made of galvanized steel profiles. Mounting system without hardware and fasteners on the front surface.	piece	2.00
12	3D letter (sign) 	Sign	Formed mortise in the frieze of the building letters "express" (English) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 7 letters.	piece	7.00
13	3D letter (sign) 	Sign	Formed mortise in the frieze of the building letters "express" (Georgian) front panel of acrylic 3mm. Internal LED backlighting by LEDs (Cree LEDs). Set of 8 letters.	piece	8.00
14	Orange strobe light 	strobe	Profile with LED illumination in compound casting, made of extruded aluminum with a polymer coating, on brackets. Includes front and backlight illumination. Designed to organize the illumination of the frieze around the perimeter of the canopy. Complete with hardware. (completed on three and a half sides of the canopy)	meter	33.30
15	Ceiling 	Ceiling	0.7mm galvanized steel suspended ceiling composed of: white panel with a width of 325 mm, docking profile, metal frame made of galvanized pipe and fittings, hardware.	m2	124.30
16	LED lightning 	LED lightning	LED Light, built into the suspended ceiling. Rectangular or square. Degree of protection against environmental impact IP65-67, operating temperature range from -30 to +50 degrees. Easy removable design for maintenance and replacement.	piece	8.00
17	column cladding 	Pillar cladding	Column cladding made of galvanized steel , 1.6 mm thick, with a polymer coating. Complete with metal frame. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height m, 2pcs from island to canopy 4.30 M	m2	17.20
18	Wall cladding cassetes Aluminium 	Wall cladding cassetes	Sheathing of the walls of the building with galvanized steel cassettes with a pattern - wood imitation. Complete with a subsystem for attaching to building structures and hardware. Installation of the facade system without visible fasteners.	m2	35.33

6		Cap	The plinth of the building is steel, made of smooth galvanized steel, the inner frame is made of galvanized steel pipe.	m2	2.65
6		Escarpments	Sheathing of window and door openings on the building is made of 1.8 mm thick aluminum with a polymer coating. The special design of slopes with the use of aluminum extrusion profiles ensures the absence of hardware on the front surfaces. The window (door) slope is volumetric. Fastened by means of the P-A08 profile, which ensures the absence of hardware on the front surfaces.	m2	11.35
19	Steel trash bin 	trash bin	Combined service unit on a fuel platform made of polymer coated steel. Includes a towel holder, a washing station for washing glasses, a box for gloves and a garbage container	piece	1.00
20	steel parapet 	steel parapet	Galvanised steel parapet 0.5 mm thickness, without metal subsystem , made on the site	m2	15.37

21	Price board 	Totem	<p>Stela price 9500 mm ,for 4 types of fuel G-Force Premium, Euro Regular, Euro diesel ,reserve). Double sided. The stela panels are made of galvanized steel with a thickness of 1.9 mm with a polymer coating .(Gulf express design) The logo is made of molded white milk acrylic with UV printing. The logo is illuminated with white LEDs.</p> <p>The price panel is made of polymer coated aluminum. Highlighting the types of fuel and the cost of fuel made by white LEDs.</p> <p>The upper information panel is made of aluminum with a polymer coating and appliqué with UV printing.</p> <p>The lower information panel of the stela is made of aluminum with a polymer coating. The information is applied using a vinyl film with UV printing.</p> <p>The stela is equipped with an infrared remote control for price lines.</p>	Piece	1.00
22	column cladding 	Pillar cladding	<p>Column cladding made of galvanized steel , 1.6 mm thick, with a polymer coating. Complete with metal frame. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support.</p> <p>Height m, 2pcs from concrete to canopy 4.50 M</p>	M2	18.00
23	column cladding 	Pillar cladding	<p>Column cladding made of galvanized steel , 1.6 mm thick, with a polymer coating. Complete with metal frame. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support.</p> <p>Height m, 2pcs from building to canopy 1.4 M</p>	M2	5.60