

Station: Fortuna (GULF)

pic	Name	Technical description	Unit	Quantity	Unit cost, \$	Cost, \$
Building						
1		Frieze	The frieze of the building, 600 mm high, with a polymer coating. Complete with substructures. Installation of panels without visible fasteners.	m2	20.00	0.00
2		3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (English) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters.	pcs	9.00	0.00
3		3D letter (sign)	Molded letters "Gulf Store" embedded in the frieze of the building (Georgian) the front panel is made of 3mm acrylic. Internal LED illumination with LEDs (Cree LEDs). Set of 9 letters.	pcs	9.00	0.00
4		Profile	The profile of the junction of the frieze to the building in the upper part with a polymer coating (orange), h = 200mm	m2	6.40	0.00
5		Parapet	Parapet 700 mm wide made of galvanized steel 0.5 mm thick. Without an internal metal frame. Fabrication at a construction site.	m2	30.00	0.00
6		Mood lighting	Stroke with LED illumination for illumination of the frieze of the building. Made of trapezoidal plastic profile with LED lighting.	m	32.00	0.00
TOTAL :						
CANOPY						
7		Frieze	The frieze of the canopy is made of rolled panels, with a polymer coating, h=900 mm. Complete with a subsystem for attaching to metal structures of the canopy and hardware. The possibility of service is provided. All hardware with an open mount is painted in the color of the panels, (3 sides)	m2	61.70	0.00
8		Frieze	Canopy frieze corner, 900mm high, made of welded aluminum in blue color. Substructures are made of galvanized steel profiles. Mounting system without hardware and fasteners on the front surface.	pcs	4.00	0.00
9		3D letter (sign)	Molded inset letters "Gulf" (English) with a front surface of 3mm thick acrylic glass. Internal LED backlight. (1 set of letters of 4 pieces)	pcs	4.00	0.00
10		3D letter (sign)	Molded inset letters "Gulf" (Georgian) with a 3 mm thick acrylic glass front surface. Internal LED backlight. (2 sets of letters of 5 pieces each)	pcs	10.00	0.00
11		Mood lighting	Profile with LED illumination in compound filling, it is made of extruded aluminum with a polymer coating, on brackets in the composition with an extruded plastic light profile. It includes front and back lighting. Designed to organize the illumination of the frieze around the perimeter of the canopy. Complete with hardware.	M	63.00	0.00
12		Ceiling	Suspended ceiling made of galvanized steel 0.7mm thick consisting of: white panel 325 mm wide, RT docking profile, metal frame made of galvanized pipe and fittings, hardware.	m2	320.70	0.00
13		LED lighting	The LED lamp is built into the suspended ceiling. Rectangular. For external use. The degree of protection is IP65. The body is cast aluminum. The luminous flux is 10600Lm, the color temperature is 5000K. Power consumption - no more than 100 watts. Operating temperature - 30...+50. Easy removable design for maintenance and replacement.	pcs	16.00	0.00
14		Parapet	The parapet is made of galvanized steel 0.5 mm thick, with locks. Without an internal metal frame. Made on the construction site.	m2	59.00	0.00
15		Profile	Transition profile of the frieze abutting to the canopy ceiling h = 0.2 m with polymer coating (white).	m2	12.60	0.00
16		Pillar cladding	The covering of the canopy support is conventionally rectangular in cross-section, made of galvanized steel with polymer coating. Complete with a subsystem for attaching the skin to the metal frame of the canopy. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 4.9m, 4pc	m2	80.36	0.00
17		Pillar cladding	The covering of the canopy support is conventionally rectangular in cross-section, made of galvanized steel with polymer coating. Complete with a subsystem for attaching the skin to the metal frame of the canopy. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 4.9m, 2pc	m2	22.54	0.00
18		Pillar cladding	The covering of the canopy support is conventionally rectangular in cross-section, made of galvanized steel with polymer coating. Complete with a subsystem for attaching the skin to the metal frame of the canopy. The height of the supports is determined by the height of the canopy, the sweep depends on the size of the core of the support. Height 1.6m, 3pc	m2	6.40	0.00
19		Information box	Intercolumn box 2x2m light. Fastening and framing profiles are made of galvanized steel with a polymer coating. Tablets are made of acrylic glass with printing or information application with vinyl films. The interior lighting is made of light-emitting diodes (LED). Complete with fasteners and hardware.	pcs	4.00	0.00
20		Protective arc steel	Protective arc for installation in front of/on the safety islands.	pcs	4.00	0.00
21		Trash bin	Combined service unit on a fuel platform made of polymer coated steel. Includes a towel holder, a washing station for washing glasses, a box for gloves and a garbage container.	pcs	4.00	0.00
TOTAL :						
					Cost without VAT	0.00
					Transportation without VAT	
					Installation without VAT	
					Total cost without VAT	0.00