FIRE PUMP STATION DATA SHEET Non- UL&FM approved		
Α		MAIN ELECTRIC PUMP
1	CAPACITY	150 GPM
2	HEAD	7 BAR
3	PUMP CASING	CAST IRON
4	IMPELLER	CAST IRON
5	SHAFT	STAINLESS STEEL
6	SHAFT SEAL	MECH. SEAL
7	MOTOR	NIDEC
	VOLTAGE	415V; 50HZ;
9	POWER	24 HP
10	SPEED	2970 RPM
11	INSULATION	CLASS F
	PROTECTION	IP 55
В		STANDBY DIESEL PUMP
1	CAPACITY	150 GPM
2	HEAD	7 BAR
_	PUMP CASING	CAST IRON
4	IMPELLER	CAST IRON
	SHAFT	STAINLESS STEEL
	SHAFT SEAL	MECH. SEAL
_	MOTOR	Diesel
	VOLTAGE	12 VDC
_	POWER	24 HP
_	SPEED	3000 RPM
_	BATTERY	12 V.
_	DIESEL TANK and EXHAUSTE	cap. 12 gal
С		JOKEY PUMP
	IMPELLER	STAINLESS STEEL
_	SHAFT	STAINLESS STEEL
	PRESSURE SWITCH	TEEMECANIQUE
_	PRESSURE VESSEL	WATER 20 LTR/10 BAR
D	- N.2555.N.2	AUTOMATIC CONTROLLER
	MILD STEAL BOX	
	AUTOMATIC PUMPS TRANSFER SWITCH	
_	TIME RELLEIES	
4	SEPARATE LIGHT INDICATORS	
Ŀ.	MANUAL SWITCH ON/OFF BUTTONS	
6	EMERGENCY STOP BUTTON	
E		ACCESSORIES
1	CHECK VALVES FOR EACH PUMPS	UL LISTED / FM APPROVED
2	GATE VALVES FOR EACH PUMPS	UL LISTED / FM APPROVED
3	WATER SUCTION MANIFOLD	DOUBLE FLANGED INLETS
_	WATER DISCHARGE MANIFOLD	DOUBLE FLANGED OUTLETS
	SWITCHING PUMPS	PRESSURE RELLEY
	AIR RELEASE VALVE	. NEOSONE NELLE I
		JOINT METAL BASEMENT FOR 3 PUMPS AND CONTROLLER AND ALL
7	PUMP STATION STANDING	OTHER ACCESSORIES

Sample picture

